

HOOD 110 I
INSULATED
HOOD-TYPE DISHWASHERS





The Kromo hood-type dishwashers offer a wide range of models, from the ones that can be equipped with the most advanced options, to the most innovative types, designed with avant-garde electronics and with all options included.

Our products have evolved together with our experience and our customers' hints and insights.

Therefore we are able to produce tailor-made models that fulfil our final customers' criteria of functionality, reliability and versatility.

Our aim is to reduce consumptions in terms of energy, water and chemical products, therefore granting the final user global savings, but also less pollution and waste of natural resources.



TOUCH PANEL

The LED panel displays the temperatures of both tank and boiler, the wash cycle and status and eventual main alarm codes for malfunctions. There are four wash cycles available. These innovations are designed to provide Kromo's customers with even more user friendly machines, maintaining the same high performances.

FEATURES HOOD 110 I

- Two wash cycles
- Hood operating start/stop functions
- Tank deep-formed bottom
- Pump filter
- S/S surface filters
- Double skin insulated hood
- Built-in rinse-aid pump
- Tank and boiler thermometres
- Easily removable basket support
- Linear or corner layouts
- Independent stainless steel wash arms and polypropylene and fiber of glass rinse arms
- Built-in water softener available

FEATURES HOOD 110 I T

- Easy and intuitive LED control panel
- Four wash cycles
- Hood operating start/stop functions
- Tank deep-formed bottom
- Built-in rinse-aid pump
- Tank and boiler thermometres
- Surface filters
- Easily removable basket support
- Double skin insulated hood
- Linear or corner layouts
- Independent stainless steel wash arms and polypropylene and fiber of glass rinse arms
- Self-cleaning cycle
- Automatic built-in water softener available

Model		Voltage	Capacity	Dimensions	Code
HOOD 110 I	2 PROGRAMS				
	RACK EQUIPMENT 2 X C40 1 X C44 2 X 15060	400 V 3N ~ 50 Hz 10,2 kW	ø 410 500x500	720x735x 1445/1880 H 100 kg GN 1/1 530x325x25 H	HOOD 110 I HOOD 110 I D

X With special basket to be ordered

Model		Voltage	Capacity	Poids	Code					
HOOD 110 I T	ELECTRONIC 4 PF	ELECTRONIC 4 PROGRAMS								
	RACK EQUIPMENT 2 X C40 1 X C44 2 X 15060	400 V 3N ~ 50 Hz 10,2 kW	ø 410 500x500	720x735x 1445/1880 H 100 kg GN 1/1 530x325x25 H	HOOD 110 I T HOOD 110 I T DA					

OPTIONS

						XP	PS	DDE	DB	
Model	220-240 \ 50 Hz	/ 380-415 V 3N 50 Hz	380-415 V 3 50 Hz	440 V 3 60 Hz	60 Hz	Extra Power	Drain Pump	Detergent Dispenser	Rinse-Aid Dispenser	
HOOD 110 I	€	•			€	€	€	€	•	
HOOD 110 I D	€	•			€	€	€	€	•	
HOOD 110 I T	€	•			€	€	€	€	•	
HOOD 110 I T DA	€	•			€	€	€	€	•	

- Standard
- □ Upon request
- ---- Not available
- I Insulated hood
- **D** Built-in water softener
- **DA** Built-in automatic water softener
- T Soft touch panel

EAC label upon request

Water supply 55 °C (not on HR version)

	DBE	TS	ВТ	WRAS	DVGW	PAP	ID	DF
Model	Peristaltic Rinse-Aid Disp.	Electr. Timer +Thermostop	Break Tank	Wras	DVGW	Booster Pump	Double Skin	Surface Filters Kit
HOOD 110 I	€	•	€	€	€	€	•	•
HOOD 110 I D	€	•				€	•	•
HOOD 110 I T	€	•	€	€	€	€	•	•
HOOD 110 I T DA	€	•				€	•	•

230-240 V 50 HZ For HOOD 110 total power 7,2 kW upon request

XP In case of cold water supply for rinse (8-55 °C) and without any heat recovery, the extra power option is mandatory.

+3000 W with standard voltage only, for other voltages please contact us. In case of cold water supply for rinse

(8-15 °C). We recommend the heat recovery option, if available on the selected model.

BT - WRAS - DVGW Booster pump included.

DVGW Components prescribed by DVGW on request (check option compatibility with the manufacturer)

Option compatibility to be confirmed by the manufacturer after verification.

ACCESSORIES

 Description	Capacity	Dimensions	Code
SLOPED GLASS BASKET	Ø 10 max	500x500x200 H	C 26
GLASS BASKET WITH GLASS SUPPORT AND ANTI-TIPPING LID		500x500x235 H	C 135
LARGE MESH BASKET	For glasses	500x500x105 H	C 44
HOLDER FOR GLASS SUPPORT	For glass support (C112-C113-C114)	500x500x50 H	C111
GLASS SUPPORT	5x5 Glass Ø 87 mm (C111)	500x500x50 H	C 112
GLASS SUPPORT	4x4 Glass Ø 110 mm (C111)	500x500x50 H	C 113
GLASS SUPPORT	6x6 Glass Ø 72 mm (C111)	500x500x50 H	C 114
PLATE BASKET	18 Plates	500x500x105 H	C 40
GASTRONORM TRAYS BASKET	6 pcs max depth 25mm	500x500x105 H	C 43/B
CUTLERY BASKET	Standard (2 pcs)	Ø 120x120 H	15060
WATER SOFTENER	12	Ø 200x500 H	DEP 12
AUTOMATIC WATER SOFTENER	12 l (max 800 l)	315x510x685 H	DEP 12-AUT

	Description	Capacity I	Dimensions	Code
	SHELF	Only for exit	600x510	K 2ME
	TABLE		650x510x860 H	K 4/65
	HOOD CONNECTION SHELF			KIT DUO
	CORNER TABLE		590x590x860 H	K 2ANG
			700x590x860 H	К 4/70В
	TABLE		1200x590x860 H	K 4/120B
			1200x590x860 H	К 4В
		Sink 500x400x270 H	1200x730x860 H	К 5
			1200x730x860 H	K 5F
			1200x730x860 H	K 55
			1500x730x860 H	К 8
		Sink 500x400x270 H	1500x730x860 H	К 8Е
	* <u>U</u>		1800x730x860 H	К 9
	0.1515		1515x620x660 H	K 7M16*
	SHELF		2315x620x660 H	K 7M24*
	GRADING TABLE WITH	Waste hole and special dimensions	1600x1000x850 H	K 7A/1600*
	RUBBER RING	upon request	2400x1000x850 H	K 7A/2400*
ρ	FLEXIBLE SHOWER comp group and lever tap, to b	plete with mixing e fixed to the wall	1000 H	К 1
AL ALA	FLEXIBLE SHOWER comp group and lever tap, to b intermediate tap		1000 H	K 1HR
		Basic model	Ø 400x570 H	K 7/1
	STAINLESS STEEL WASTE BIN	With wheels	Ø 400x570 H	К 7/2
		With wheels and	Ø 400×570 H	К 7/3
* Wooden cage +2% minimum +	£			'

^{*} Wooden cage +2% minimum + € Special dimensions for tables upon request Tables shown in right-to-left version



KROMO ALI GROUP SRL

Via Mestre, 3 31033 Castelfranco Veneto (TV) T: +39 0423 734580 F: +39 0423 734581 kromo@kromo-ali.com

SERVICE:

T. +39 0423 734593 F: +39 0423 734592 E: service@kromo-ali.com

www.kromo-ali.com

Edition 05.2023

an Ali Group Company

