



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
---	---------------------------	---	----------------------	---	-------------------

TECHNICAL DATA	STD	THREE-PHASE	UK
<b>EXTERNAL DIMENSIONS</b>			
width		450 mm	
depth		535 mm	
height		700 mm	
WEIGHT		37 kg	
VOLTAGE	230V 50Hz	400V 3N 50Hz	240V 50Hz
POWER REQUIRED	3200 W	4400 W	3010 W
WATER HARDNESS		2-8 °F	
INLET WATER PRESSURE		200-400 kPa	
<b>CROCKERY DIMENSIONS</b>			
plates diameter (LS version)		295mm	
dishes max. height		305mm	
RACK DIMENSIONS		400X400mm	
RACK EQUIPMENT		2XC121 - 1X10728 - 1X15060	
WASHING CYCLES (sec)		1(120)	
<b>WATER SUPPLY 55°C</b>			
racks/h(*) <sup>(1)</sup>		30	
<b>WATER SUPPLY 10°C</b>			
racks/h(*) <sup>(1)</sup>	16	22	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)		1.8 L	
BOILER CAPACITY		3.4 L	
BOILER HEATING ELEMENT	2800 W	4000 W	2610 W
RINSING TEMPERATURE (SET)		85°C	
TANK CAPACITY		14.5 L	
TANK HEATING ELEMENT		1250 W	
TANK TEMPERATURE (SET)		55°C	
PUMP POWER		400 W (185 L/min <sup>***</sup> )	
DRAIN PUMP (optional)	25 W	h MAX draining 0.8m (40 L/min <sup>***</sup> )	
NOISE (dB(A)±0.7)		60.6(CF)	61.2(LS)

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.