AQUA 50 MONO

GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR

Range: AQUA

The glass and dishwashers of the AQUA series are ideal for bars, pubs, restaurants and hotels.
These undercounter machines, with a redesigned control panel, feature a wide loading capacity granting the highest performance at a reasonable price. According to the user's needs the machine can be customized thanks to many optional features such as water softener, detergent dispenser and drain pump.

FEATURES

- Solid structure in AISI 304 S/S
- Sound and heat proof double skin door
- Door with anti-shock system
- Deep-drawn and sloped tank for a perfect total drain
- Non-drip roof to safeguard the hygiene of the freshly washed dishes
- Innovative system of grouped wash and rinse arms made of composite materials
- Easy to remove nozzles to help with daily cleaning operations
- Overflow and drain pipes integrated system for a triple protection of the wash pump
- Non-return valve to prevent the water backflow
- Thermostop system: the rinse starts only when the water in boiler reaches 85 °C
- Rinse aid dispenser

OPTIONS

- Special voltages
- Drain pump
- Built-in peristaltic detergent dispenser
- Peristaltic rinse aid dispenser
- Surface filters

Option compatibility to be confirmed by the manufacturer after verification

CAPACITY

320 H | Ø 345 | 500x500

RACK EQUIPMENT
- 1 X C40
- 1 X C44
- 1 X 15060

AQUA 50 MONO

GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR



TECHNICAL FEATURES		
EXTERNAL DIMENSIONS		
Width	mm	590
Depth	mm	600
Height (screwed foot)	mm	850
Weight (standard version)	kg	57
TECHNICAL DATA		
Basket dimensions	mm	500x500
Glasses maximum useful height	mm	320
Maximum dish diameter	mm	345
Maximum level of water discharge	mm	95
Water inlet temperature	°C	55
Maximum inlet water hardness	°f	8
Inlet water pressure	kPa	200 - 400
Tank capacity	l	29
Tank heating element	kW	2.7
Boiler capacity	l	5.7
Boiler heating element	kW	2.8
Wash pump power	kW	0.65
Wash pump flow rate	l/min	340
Sound pressure level	dB(A)	< 70

POWER SUPPLY DATA		
Supply voltage		220-240 V 50 Hz
Total installed power	kW	3.45

AQUA 50 MONO

GLASS & DISHWASHERS WITH DOUBLE SKIN DOOR

CYCLES		
Cycle number		1
Cycle length	s	120
Cycle productivity (racks/h) - 55°C inlet water		30
Cycle productivity (racks/h) - 10°C inlet water		14
Cycle water consumption	l	2.3
Rinsing temperature setting	°C	85
Washing temperature setting	°C	55

Standard Thermostop. In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.

N.B. ACCORDING TO THE LAW, WE RESERVE OWNERSHIP OF THIS DESIGN OR MODEL WITH A PROHIBITION ON REPRODUCING IT OR MAKING IT KNOWN TO THIRD PARTIES OR COMPETITIVE COMPANIES WITHOUT OUR WRITTEN CONSENT