



 WATER CONNECTION 3/4" GAS	 DRAINING PIPE Ø 24mm	 ELECTRICAL SUPPLY
---	--	--

TECHNICAL DATA	STD
EXTERNAL DIMENSIONS	
width	590 mm
depth	600 mm
height	850 mm
WEIGHT	
	56.5 kg
VOLTAGE	
	230V 50Hz
POWER REQUIRED	
	3450 W
WATER HARDNESS	
	2-8 °F
INLET WATER PRESSURE	
	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter	345 mm
dishes max. height	320 mm
RACK DIMENSIONS	
	500X500 mm
RACK EQUIPMENT	
	1XC40 - 1XC44 - 1X15060
WASHING CYCLES (sec)	
	1 (120)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	30
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	
	2.3 L
BOILER CAPACITY	
	5.7 L
BOILER HEATING ELEMENT	
	2800 W
RINSING TEMPERATURE (SET)	
	85°C
TANK CAPACITY	
	29 L
TANK HEATING ELEMENT	
	2700 W
TANK TEMPERATURE (SET)	
	55°C
PUMP POWER	
	650 W (340 L/min ^{***})
DRAIN PUMP (optional)	
	25 W h MAX draining 0.8m(40 L/min ^{***})
NOISE	
	63 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.