



TECHNICAL DATA		STANDARD				
<b>EXTERNAL DIMENSIONS</b>						
width		590 mm				
depth		600 mm				
height		1290 mm				
<b>WEIGHT</b>						
68.5 kg						
<b>VOLTAGE</b>						
400V 3N 50Hz						
<b>POWER REQUIRED</b>						
6900 W						
<b>WATER HARDNESS</b>						
2-8 °F						
<b>INLET WATER PRESSURE</b>						
200-400 kPa						
<b>CROCKERY DIMENSIONS</b>						
plates diameter		380 mm				
glasses max. height		355 mm				
<b>RACK DIMENSIONS</b>						
500X500 mm						
<b>RACK EQUIPMENT</b>						
1XC40 - 1XC44 - 1X15060						
<b>WASHING CYCLES</b> (sec)						
	1(60)	2(90)	3(120)	4(180)	----	
<b>WATER SUPPLY 55°C</b>						
racks/h <sup>(*)</sup> ( <sup>1</sup> )	<b>60</b>	<b>40</b>	<b>30</b>	<b>20</b>	--	
<b>WATER SUPPLY 10°C</b>						
racks/h <sup>(*)</sup> ( <sup>1</sup> )	<b>26</b>	<b>26</b>	<b>26</b>	<b>20</b>	--	
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)						
2.3 L						
<b>BOILER CAPACITY</b>						
5.7 L						
<b>BOILER HEATING ELEMENT</b>						
6000 W						
<b>RINSING TEMPERATURE (SET)</b>						
85°C						
<b>TANK CAPACITY</b>						
29 L						
<b>TANK HEATING ELEMENT</b>						
2700 W						
<b>TANK TEMPERATURE (SET)</b>						
55°C						
<b>PUMP POWER</b>						
900 W (500 L/min <sup>***</sup> )						
<b>DRAIN PUMP (optional)</b>						
25 W h MAX drainig 0.8m (40 L/min <sup>***</sup> )						
<b>NOISE</b>						
63 dB(A)						

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.