



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA		STD		
EXTERNAL DIMENSIONS				
width		400 mm		
depth		495 mm		
height		595 mm		
WEIGHT				
		28 kg		
VOLTAGE				
		230V 50Hz		
POWER REQUIRED				
		2590 W		
WATER HARDNESS				
		2-8 °F		
INLET WATER PRESSURE				
		200-400 kPa		
CROCKERY DIMENSIONS				
plates diameter		--- mm		
dishes max. height		195 mm		
RACK DIMENSIONS				
		350X350 mm		
RACK EQUIPMENT				
		2X10730- 1X10728 - 1X15060		
WASHING CYCLES (s)				
		1<90>	2<120>	3<180>
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾		38	30	20
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾		17	17	17
WATER CONSUMPTION / CYCLE (water pressure 200kPa)				
		1.4 L		
BOILER CAPACITY				
		2.5 L		
BOILER HEATING ELEMENT				
		2400 W		
RINSING TEMPERATURE (SET)				
		85°C		
TANK CAPACITY				
		9.5 L		
TANK HEATING ELEMENT				
		1250 W		
TANK TEMPERATURE				
		55°C		
PUMP POWER				
		190 W (<120 L/min***)		
DRAIN PUMP (optional)				
		25 W h MAX drainig 0.8m (<40 L/min***)		
NOISE				
		60.6±0.7 dB(A)		

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.