



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
---	---------------------------	---	----------------------	--	-------------------

TECHNICAL DATA	STD
<b>EXTERNAL DIMENSIONS</b>	
width	400 mm
depth	495 mm
height	585 mm
<b>WEIGHT</b>	
	28 kg
<b>VOLTAGE</b>	
	230V 50Hz
<b>POWER REQUIRED</b>	
	2590 W
<b>WATER HARDNESS</b>	
	2-8 °F
<b>INLET WATER PRESSURE</b>	
	200-400 kPa
<b>CROCKERY DIMENSIONS</b>	
plates diameter	--- mm
dishes max. height	195 mm
<b>RACK DIMENSIONS</b>	
	350X350 mm
<b>RACK EQUIPMENT</b>	
	2X10730- 1X10728 - 1X15060
<b>WASHING CYCLES</b> (s)	
	1 (120)
<b>WATER SUPPLY 55°C</b>	
racks/h(*) <sup>(1)</sup>	30
<b>WATER SUPPLY 10°C</b>	
racks/h(*) <sup>(1)</sup>	18
<b>WATER CONSUMPTION / CYCLE</b> (water pressure 200kPa)	
	1.4 L
<b>BOILER CAPACITY</b>	
	2.5 L
<b>BOILER HEATING ELEMENT</b>	
	2400 W
<b>RINSING TEMPERATURE (SET)</b>	
	85°C
<b>TANK CAPACITY</b>	
	9.5 L
<b>TANK HEATING ELEMENT</b>	
	1250 W
<b>TANK TEMPERATURE</b>	
	55°C
<b>PUMP POWER</b>	
	190 W (120 L/min <sup>***</sup> )
<b>DRAIN PUMP (optional)</b>	
	25 W h MAX drainig 0.8m (40 L/min <sup>***</sup> )
<b>NOISE</b>	
	60.6±0.7 dB(A)

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.