



 WATER CONNECTION 3/4" GAS	 DRAINING PIPE Ø 24mm	 ELECTRICAL SUPPLY
---	--	---

TECHNICAL DATA	STD		
EXTERNAL DIMENSIONS			
width	450 mm		
depth	535 mm		
height	710 mm		
WEIGHT			
	37 kg		
VOLTAGE			
	230V 50Hz		
POWER REQUIRED			
	2590 W		
WATER HARDNESS			
	2-8 °F		
INLET WATER PRESSURE			
	200-400 kPa		
CROCKERY DIMENSIONS			
plates diameter (LS version)	295mm		
dishes max. height	305mm		
RACK DIMENSIONS			
	400X400mm		
RACK EQUIPMENT			
	2XC121 - 1X10728 - 1X15060		
WASHING CYCLES (s)			
	1<90>	2<120>	3<180>
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾	31	30	20
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	14	14	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)			
	1.8 L		
BOILER CAPACITY			
	3.4 L		
BOILER HEATING ELEMENT			
	2400 W		
RINSING TEMPERATURE (SET)			
	85°C		
TANK CAPACITY			
	14.5 L		
TANK HEATING ELEMENT			
	1250 W		
TANK TEMPERATURE (SET)			
	55°C		
PUMP POWER			
	190 W (120 L/min ^{***})		
DRAIN PUMP (optional)			
	25 W h MAX drainig 0.8m (40 L/min ^{***})		
NOISE			
	60.6 (dB(A)±0.7)		

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.