



 WATER CONNECTION 3/4" GAS	 DRAINING PIPE Ø 24mm	 ELECTRICAL SUPPLY
---	--	---

TECHNICAL DATA	STD
EXTERNAL DIMENSIONS	
width	450 mm
depth	535 mm
height	700 mm
WEIGHT	37 kg
VOLTAGE	230V 50Hz
POWER REQUIRED	2590 W
WATER HARDNESS	2-8 °F
INLET WATER PRESSURE	200-400 kPa
CROCKERY DIMENSIONS	
plates diameter (LS version)	295mm
dishes max. height	305mm
RACK DIMENSIONS	400X400mm
RACK EQUIPMENT	2XC121 - 1X10728 - 1X15060
WASHING CYCLES (s)	1 (120)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	30
WATER SUPPLY 10°C	
racks/h(*) ⁽¹⁾	16
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L
BOILER CAPACITY	3.4 L
BOILER HEATING ELEMENT	2400 W
RINSING TEMPERATURE (SET)	85°C
TANK CAPACITY	14.5 L
TANK HEATING ELEMENT	1250 W
TANK TEMPERATURE (SET)	55°C
PUMP POWER	190 W (120 L/min ^{***})
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})
NOISE (dB(A)±0.7)	60.6(CF) 61.2 (LS)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.