



TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width	600 mm				
depth	610 mm				
height	850 mm				
WEIGHT	70 kg				
VOLTAGE	400V 3N 50Hz (380/400V 3 60Hz "Marina")				
POWER REQUIRED	6650 W				
WATER HARDNESS	2-8 °f				
INLET WATER PRESSURE	200-400 kPa				
CROCKERY DIMENSIONS					
useful neck diameter / max. bottle diameter	16 + 50 mm / 113 mm				
bottle height	325 mm				
RACK DIMENSION	500 x 500 mm				
RACK EQUIPMENT	1 x DWC140 - 1 x DWC44				
WASHING CYCLES (s)	1(80")	2(100")	3(180")	4(240")	
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾	45	36	20	15	
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾	15	10	10	10	
WATER CONSUMPTION / CYCLE	5 l	6,5 l			
BOILER CAPACITY	11 l				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	70 °C	85 °C			
TANK CAPACITY	16,5 l				
TANK HEATING ELEMENT	2700 W (2230W "Marina")				
TANK TEMPERATURE (SET)	55 °C				
PUMP POWER	650 W (340 l/min***)				
DRAIN PUMP (optional)	25 W h MAX scarico 0,8 m (40 l/min***)				
NOISE	61,3 ± 0,7 dB(A)				

(*) STANDARD TERMOSTOP (*)MAXIMUM FLOW RATE**

(1) In caso di alimentazione con acqua fredda e/o in caso di più lavaggi consecutivi si potrebbero allungare i tempi del riscaldamento del risciacquo finale e del lavaggio, fino al raggiungimento della temperatura ottimale. Conseguentemente, il tempo totale del ciclo di lavaggio potrebbe aumentare.