



TECHNICAL DATA		
EXTERNAL DIMENSIONS	STANDARD	LS
width	430mm	
depth	490mm	
height	680mm	
WEIGHT	32 kg	
VOLTAGE	230V 50Hz	
POWER REQUIRED	2590 W	2800 W
WATER HARDNESS	2-8 °F	
INLET WATER PRESSURE	200-400 MPa	
CROCKERY DIMENSIONS		
plates diameter	---	285mm
dishes max. height	290mm	
RACK DIMENSION	370X370	
RACK EQUIPMENT	2XC10 - 1X10728 - 1X15060	
WASHING CYCLES (sec)	1(120)	
WATER SUPPLY 55°C		
racks/h(*) ⁽¹⁾	30	
WATER SUPPLY 10°C		
racks/h(*) ⁽¹⁾	14	
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L	
BOILER CAPACITY	3 L	
BOILER HEATING ELEMENT	2400 W	
RINSING TEMPERATURE (SET)	85 °C	
TANK CAPACITY	12.5 L	
TANK HEATING ELEMENT	1250 W	
TANK TEMPERATURE (SET)	55 °C	
PUMP POWER	190 W(120 L/min ^{***})	400 W(185 L/min ^{***})
DRAIN PUMP (optional)	25 W h MAX draining 0.8m (40 L/min ^{***})	
NOISE (dB(A)±0.7)	60.6	61.2

(*) STANDARD TERMOSTOP

(^{***}) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.