



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	----------------------------------	--	-----------------------------	--	--------------------------

TECHNICAL DATA	STD	THREE-PHASE	UK
EXTERNAL DIMENSIONS			
width		460mm	
depth		545mm	
height		715mm	
WEIGHT			
		38 kg	
VOLTAGE	230V 50Hz	400V 3N 50Hz	240V 50Hz
POWER REQUIRED	3200 W	4400 W	3010 W
WATER HARDNESS		2-8 °F	
INLET WATER PRESSURE		200-400 kPa	
CROCKERY DIMENSIONS			
plates diameter		295mm	
dishes max. height		305mm	
RACK DIMENSIONS			
		400X400mm	
RACK EQUIPMENT			
		2XC121 - 1X10728 - 1X15060	
WASHING CYCLES (sec)		1(120)	
WATER SUPPLY 55°C			
racks/h(*) ⁽¹⁾		30	
WATER SUPPLY 10°C			
racks/h(*) ⁽¹⁾	16	22	14
WATER CONSUMPTION / CYCLE (water pressure 200kPa)			
		1.8 L	
BOILER CAPACITY			
		3.4 L	
BOILER HEATING ELEMENT	2800 W	4000 W	2610 W
RINSING TEMPERATURE (SET)			
		85°C	
TANK CAPACITY			
		15.5 L	
TANK HEATING ELEMENT			
		1250 W	
TANK TEMPERATURE (SET)			
		55°C	
PUMP POWER			
		400 W (185 L/min ^{***})	
DRAIN PUMP (optional)			
		25 W h MAX drainig 0.8m (40 L/min ^{***})	
ACOUSTIC PRESSURE			
		61.2 (dB(A)±0.7)	

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.