



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD	
EXTERNAL DIMENSIONS		
width	595 mm	
depth	610 mm	
height	845 mm	
WEIGHT		
61 kg		
VOLTAGE		
230V 50Hz		
POWER REQUIRED		
3450 W		
WATER HARDNESS		
2-8 °F		
INLET WATER PRESSURE		
200-400 kPa		
CROCKERY DIMENSIONS		
plates diameter	325 mm	
dishes max. height	310 mm	
RACK DIMENSIONS		
500X500 mm		
RACK EQUIPMENT		
1XC40 - 1XC44 - 1X15060		
WASHING CYCLES	(sec)	
	1 (120)	2 (180)
WATER SUPPLY 55°C		
racks/h(*) ⁽¹⁾	30	20
WATER SUPPLY 10°C		
racks/h(*) ⁽¹⁾	12	12
WATER CONSUMPTION / CYCLE (water pressure 200kPa)		
2.3 L		
BOILER CAPACITY		
5.7 L		
BOILER HEATING ELEMENT		
2800 W		
RINSING TEMPERATURE (SET)		
85°C		
TANK CAPACITY		
27 L		
TANK HEATING ELEMENT		
2700 W		
TANK TEMPERATURE (SET)		
55°C		
PUMP POWER		
650 W (340 L/min ^{***})		
DRAIN PUMP (optional)		
25 W h MAX drainig 0.8m (40 L/min ^{***})		
NOISE		
59.3 dB(A)		

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.