



TECHNICAL DATA		STANDARD			
EXTERNAL DIMENSIONS					
width	595 mm				
depth	610 mm				
height	845 mm				
WEIGHT	61 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	5150 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
CROCKERY DIMENSIONS					
plates diameter	325 mm				
glasses max. height	310 mm				
RACK DIMENSIONS	500X500 mm				
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060				
WASHING CYCLES (sec)	1<60>	2<90>	3<120>	4<180>	
WATER SUPPLY 55°C					
racks/h ^(*) (1)	60	40	30	20	
WATER SUPPLY 10°C					
racks/h ^(*) (1)	20	20	20	20	
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L				
BOILER CAPACITY	5.7 L				
BOILER HEATING ELEMENT	4500 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	27 L				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
PUMP POWER	650 W (340 L/min ^{***})				
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})				
NOISE	59.3 dB(A)				

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.