



	WATER CONNECTION 3/4" GAS		DRAINING PIPE Ø 24mm		ELECTRICAL SUPPLY
--	---------------------------	--	----------------------	--	-------------------

TECHNICAL DATA	STD	
EXTERNAL DIMENSIONS		
width	595 mm	
depth	610 mm	
height	845 mm	
WEIGHT	61 kg	
VOLTAGE	400V 3N 50Hz	
POWER REQUIRED	5150 W	
WATER HARDNESS	2-8 °F	
INLET WATER PRESSURE	200-400 kPa	
CROCKERY DIMENSIONS		
plates diameter	325 mm	
dishes max. height	310 mm	
RACK DIMENSIONS	500X500 mm	
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060	
WASHING CYCLES (sec)	1 (120)	2 (180)
WATER SUPPLY 55°C		
racks/h(*) ⁽¹⁾	30	20
WATER SUPPLY 10°C		
racks/h(*) ⁽¹⁾	21	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.3 L	
BOILER CAPACITY	5.7 L	
BOILER HEATING ELEMENT	4500 W	
RINSING TEMPERATURE (SET)	85°C	
TANK CAPACITY	27 L	
TANK HEATING ELEMENT	2700 W	
TANK TEMPERATURE (SET)	55°C	
PUMP POWER	650 W (340 L/min ^{***})	
DRAIN PUMP (optional)	25 W h MAX drainig 0.8m (40 L/min ^{***})	
NOISE	59.3 dB(A)	

(*) STANDARD TERMOSTOP

(**) MAXIMUM FLOW RATE

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.