



load capacity trays:
 -6 gn 1/1 max depth 65mm
 -3 gn 1/1 max depth 230mm
 -2 gn 2/1 max depth 140mm
 -1 gn 2/1 max depth 500mm

	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 32mm
	ELECTRICAL SUPPLY

TECHNICAL DATA	
EXTERNAL DIMENSIONS	
width	1095 mm
depth	910 mm
height	1910/2020(open door) mm
WEIGHT(basic version)	303 kg
VOLTAGE	400V 3N 50Hz
POWER REQUIRED	12975 W
WATER HARDNESS	2-8 °F
INLET WATER PRESSURE	200-400 kPa
CROCKERY DIMENSIONS	
trays max. height	635 mm

RACK DIMENSIONS	
Ø735X240 mm	
RACK EQUIPMENT	
1X96100-1X96101-1X96102-1X96103-1X96104-1X96105-1X96135-4X96136	
WASHING CYCLES water/granules(Min)	1/2(4) 3/4(6) 5/6(8) 7/8(10) 9/10(12) 11/12(15)
WATER SUPPLY 55°C	
racks/h(*) ⁽¹⁾	15 10 7 6 5 4
WATER SUPPLY 15°C	
racks/h(*) ⁽¹⁾	15 10 7 6 5 4
WATER CONSUMPTION / CYCLE	4.4 L
BOILER CAPACITY	20 L
BOILER HEATING ELEMENT	9000 W
RINSING TEMPERATURE (SET)	85°C
TANK CAPACITY	103 L
TANK HEATING ELEMENT	9000 W
TANK TEMPERATURE (SET)	55°C
WASHING PUMP POWER	3780 W (900 L/min ^{***})
RINSING PUMP POWER	250 W (150 L/min ^{***})
OPERATING NOISE	79 dB(A)

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.