



TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width	(inch)	28 3/8"			
depth	(inch)	28 15/16"			
height	(inch)	56 7/8" / 74 1/16"			
WEIGHT(basic version)	(lbs)	253,5			
VOLTAGE		220-240 V 3 ph 60Hz			
POWER REQUIRED	(W)	10750 W			
WATER HARDNESS		2 - 8 °F			
INLET WATER PRESSURE		20 - 95 psi (170 - 620 kPa)			
CROCKERY DIMENSIONS					
plates diameter	(inch)	16 1/8"			
tray max. dimension	(inch)	GASTRONORM 1/1			
RACK DIMENSIONS	(inch)	20x20"			
RACK EQUIPMENT		2xC40 - 1xC44 - 2x15060			
WASHING CYCLES	(s)	1 (120)	2 (180)	3 (240)	4 (300) 5 (360)
WATER SUPPLY 131°F					
racks/h(*) ⁽¹⁾		30	20	15	12 10
WATER SUPPLY 50°F					
racks/h(*) ⁽¹⁾		20	20	15	12 10
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	[gal(US)]	0,69			
BOOSTER CAPACITY	[gal(US)]	3,96			
BOOSTER HEATING ELEMENT	(W)	9000 W			
RINSING TEMPERATURE (SET)		185°F			
RINSING PRESSURE		104 - 172 kPa (15 - 25 psi)			
TANK CAPACITY	[gal(US)]	11,1			
TANK HEATING ELEMENT	(W)	2700 W			
TANK TEMPERATURE (SET)		160°F			
PUMP POWER	(W)	1750 W			
DRAIN PUMP		43 W h max draining 31 1/2" (10,78 gal(US))			
NOISE		66,4±0.7 dB(A)			

(*) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE