



(***) MIN 130-MAX 200 mm

TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width	720 mm				
depth	735 mm				
height	1445/1880(open hood) mm				
WEIGHT(basic version)	115 kg				
VOLTAGE	400V 3N 50Hz (380/400V 3 60Hz "Marina")				
POWER REQUIRED	10490 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
CROCKERY DIMENSIONS					
plates diameter	410 mm				
trays max. dimension	GASTRONORM 1/1 (530x325)				
RACK DIMENSION	500X500 mm				
RACK EQUIPMENT	2XC40 - 1XC44 - 2X15060				
WASHING CYCLES (sec)	1 (50)	2 (90)	3 (120)	4 (180)	----
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾	60	40	30	20	----
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾	30	30	30	20	----
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.8 L				
BOILER CAPACITY	10 L				
BOILER HEATING ELEMENT	9000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	42 L				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
PUMPS POWER	1490 W (800 L/min ^{***})				
DRAIN PUMP (optional)	25 W (40 L/min ^{***})				
NOISE	66,4±0.7 dB(A)				

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.