

	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 28mm
	ELECTRICAL SUPPLY

(\*\*\*) MIN 130-MAX 200 mm

TECHNICAL DATA					
<b>EXTERNAL DIMENSIONS</b>					
width	720 mm				
depth	735 mm				
height	1445/1915(open hood) mm				
WEIGHT(basic version)	104 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	10490 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
<b>CROCKERY DIMENSIONS</b>					
plates diameter	410 mm				
trays max. dimension	600X400 mm				
RACK DIMENSION	500X500+SPECIAL STEEL RACK 500X600 mm				
RACK EQUIPMENT	1XC44 - 1XC86/A - 1X11600054				
WASHING CYCLES (sec)	1 (50)	2 (90)	3 (120)	4 (180)	----
<b>WATER SUPPLY 55°C</b>					
racks/h(*) <sup>(1)</sup>	72	40	30	20	--
<b>WATER SUPPLY 10°C</b>					
racks/h(*) <sup>(1)</sup>	35	35	30	20	--
WATER CONSUMPTION / CYCLE	2.6 l				
BOILER CAPACITY	15 l				
BOILER HEATING ELEMENT	9000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	42 l				
TANK HEATING ELEMENT	2700 W				
TANK TEMPERATURE (SET)	55°C				
PUMPS POWER washing	1490 W (800 l/min <sup>***</sup> )				
DRAIN PUMP (optional)	25 W (40 l/min <sup>***</sup> )				
NOISE	66,4±0.7 dB(A)				

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.