



TECHNICAL DATA					
EXTERNAL DIMENSIONS					
WIDTH		27 ¼ inch (690 mm)			
DEPTH		31 ½ inch (800 mm)			
HEIGHT		86 / 90 ¼ inch (2185/2290 mm porta aperta)			
WEIGHT		364 lb (165 kg)			
VOLTAGE (V)		208 3 ph 60 Hz	220-240 3 ph 60 Hz		480 3 ph 60 Hz
POWER REQUIRED		13050 W	13580 W		13050 W
WATER HARDNESS		< 8 °f			
WATER CONDUCTIVITY		> 200 µS/cm			
INLET WATER PRESSURE		25 - 90 PSI (170 - 600 kPa)			
USEFUL HEIGHT AND RACKS					
USEFUL HEIGHT		31 ¾ inch (805 mm)			
RACK DIMENSIONS		21 ¾ x 26 ¼ inch (550 x 665 mm)			
RACK EQUIPMENT		1XC86/A - 1XC87/B - 1XC97/A - 1XC100			
WASHING CYCLES (min)		1 (5,5)	2 (6,5)	3 (8,5)	4 (10,5)
WATER SUPPLY 50-60 °F					
RACKS/h (*) (1)		10	9	7	5
WATER CONSUMPTION / CYCLE		1,1 US gal lqd (4 l)			
BOILER CAPACITY		4 US gal lqd (15 l)			
BOILER HEATING ELEMENT		6000 W			
RINSING TEMPERATURE (SET)		185 °F (85 °C)			
TANK CAPACITY		13,2 US gal lqd (50 l)			
TANK HEATING ELEMENT		5000 W			
TANK TEMPERATURE (SET)		165 °F (74 °C)			
WASHING PUMP POWER		2000 W , 250 US gal lqd/min*** (950 l/min***)			
RINSING PUMP POWER		250 W , 39,5 US gal lqd/min*** (150 l/min***)			
DRAIN PUMP (OPTIONAL)		30 W , 5,3 US gal lqd/min*** (20 l/min***)			
ACOUSTIC PRESSURE		(70 ± 2,5) dB(A)			