



| TECHNICAL DATA | | | | | |
|----------------------------|--------------------------------------|---------|---------|---------|------|
| EXTERNAL DIMENSIONS | | | | | |
| width | 690 mm | | | | |
| depth | 800 mm | | | | |
| height | 2165/2270mm (door open) | | | | |
| WEIGHT(basic version) | 165 kg | | | | |
| VOLTAGE | 400V 3N 50Hz | | | | |
| POWER REQUIRED | 8000 W | | | | |
| WATER HARDNESS | < 8 °F | | | | |
| WATER CONDUCTIVITY | > 200 µS/cm | | | | |
| INLET WATER PRESSURE | 200-400 kPa | | | | |
| CROCKERY DIMENSIONS | | | | | |
| size allowed | 805 mm | | | | |
| RACK DIMENSIONS | 550X665 mm | | | | |
| RACK EQUIPMENT | 1XC86/A - 1XC87/B - 1XC97/A - 1XC100 | | | | |
| WASHING CYCLES (sec) | 1 (180) | 2 (300) | 3 (420) | 4 (540) | ---- |
| WATER SUPPLY 55°C | | | | | |
| racks/h(*) ⁽¹⁾ | -- | -- | -- | -- | -- |
| WATER SUPPLY 10°C | | | | | |
| racks/h(*) ⁽¹⁾ | 13 | 12 | 8 | 6,5 | -- |
| WATER CONSUMPTION / CYCLE | 4,2 l | | | | |
| BOILER CAPACITY | 15 l | | | | |
| BOILER HEATING ELEMENT | 6000 W | | | | |
| RINSING TEMPERATURE (SET) | 85°C | | | | |
| TANK CAPACITY | 50 l | | | | |
| TANK HEATING ELEMENT | 3000 W | | | | |
| TANK TEMPERATURE (SET) | 60°C | | | | |
| WASHING PUMP POWER | 2000 W (810 l/min ^{***}) | | | | |
| RINSING PUMP POWER | 250 W (150 l/min ^{***}) | | | | |
| DRAIN PUMP (optional) | 190 W (120 l/min ^{***}) | | | | |
| ACOUSTIC PRESSURE | 63.8 dB(A) | | | | |

(*) STANDARD TERMOSTOP (CAN NOT BE DISABLED)

(***) MAXIMUM FLOW RATE

- STANDARD ENERGY SAVING (CAN NOT BE DISABLED)

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.