

	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 32 - Ø 40 DRAINING PIPE (DRAIN PUMP) Ø 28
	ELECTRICAL SUPPLY

TECHNICAL DATA					
EXTERNAL DIMENSIONS					
width	690 mm				
depth	800 mm				
height	1890/2270mm (door open)				
WEIGHT(basic version)	155 kg				
VOLTAGE	400V 3N 50Hz				
POWER REQUIRED	8000 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200-400 kPa				
CROCKERY DIMENSIONS					
size allowed	805 mm				
RACK DIMENSIONS	550X665 mm				
RACK EQUIPMENT	1XC86/A - 1XC87/B - 1XC97/A - 1XC100				
WASHING CYCLES (sec)	1 (120)	2 (240)	3 (360)	4 (480)	----
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾	30	15	10	7,5	--
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾	15	15	10	7,5	--
WATER CONSUMPTION / CYCLE	4,2 l				
BOILER CAPACITY	15 l				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	85°C				
TANK CAPACITY	50 l				
TANK HEATING ELEMENT	3000 W				
TANK TEMPERATURE (SET)	60°C				
WASHING PUMP POWER	2000 W (810 l/min ^{***})				
RINSING PUMP POWER	250 W (150 l/min ^{***})				
DRAIN PUMP (optional)	190 W (120 l/min ^{***})				
ACOUSTIC PRESSURE	63.8 dB(A)				

(*) STANDARD TERMOSTOP (CAN NOT BE DISABLED)

(***) MAXIMUM FLOW RATE

- STANDARD ENERGY SAVING (CAN NOT BE DISABLED)

(†) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.