



## TECHNICAL DATA

<b>width</b>	840 mm			
<b>depth</b>	885 mm			
<b>height</b>	2140 mm			
<b>WEIGHT(basic version)</b>	218 kg			
<b>VOLTAGE</b>	400V 3N 50Hz			
<b>POWER REQUIRED</b>	12500 W			
<b>WATER HARDNESS</b>	< 8 °F			
<b>WATER CONDUCTIVITY</b>	> 200 µS/cm			
<b>INLET WATER PRESSURE</b>	200-400 kPa			
<b>size allowed</b>	645 mm			
<b>RACK DIMENSIONS</b>	700x700 mm			
<b>RACK EQUIPMENT</b>	1XC86/A - 1XC97/A - 1X91100			
<b>WASHING CYCLES</b> (min)	1 (4)	2 (7)	3 (10)	4 (13)
<b>racks/h(*) (1)</b>	15	8	6	4
<b>WATER CONSUMPTION / CYCLE</b>	4,3 L			
<b>BOILER CAPACITY</b>	15 L			
<b>BOILER HEATING ELEMENT</b>	9000 W			
<b>RINSING TEMPERATURE (SET)</b>	85°C			
<b>TANK CAPACITY</b>	82 L			
<b>TANK HEATING ELEMENT</b>	6000 W			
<b>TANK TEMPERATURE (SET)</b>	55°C			
<b>WASHING PUMP POWER</b>	1750 W (800 l/min <sup>***</sup> ) x 2			
<b>RINSING PUMP POWER</b>	250 W (150 l/min <sup>***</sup> )			
<b>DRAIN PUMP (optional)</b>	190 W (120 l/min <sup>***</sup> )			
<b>ACOUSTIC PRESSURE</b>	69,9 dB(A)			

(\*) STANDARD THERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(1) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.