



	WATER CONNECTION 3/4" GAS / 55°C
	WATER CONNECTION 3/4" GAS / 10°C NO OSMOTIC WATER
	DRAINING PIPE Ø 32 - Ø 40 DRAINING PIPE ( DRAIN PUMP ) Ø 28
	ELECTRICAL SUPPLY

TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	990 mm			
depth	885 mm			
height	2140 mm			
WEIGHT(basic version)	240 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	13360 W			
WATER HARDNESS	< 8 °F			
WATER CONDUCTIVITY	> 200 µS/cm			
INLET WATER PRESSURE	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
size allowed	645 mm			
RACK DIMENSIONS	850X725 mm			
RACK EQUIPMENT	1XC86/A - 1XC97/A - 1X92100			
WASHING CYCLES (min)	1 (4)	2 (7)	3 (10)	4 (13)
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(1)</sup>	15	8	6	4
WATER CONSUMPTION / CYCLE	4,3 L			
BOILER CAPACITY	15 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	82 L			
TANK HEATING ELEMENT	6000 W			
TANK TEMPERATURE (SET)	55°C			
WASHING PUMP POWER	2180 W (810 l/min <sup>***</sup> ) × 2			
RINSING PUMP POWER	250 W (150 l/min <sup>***</sup> )			
DRAIN PUMP (optional)	190 W (120 l/min <sup>***</sup> )			
ACOUSTIC PRESSURE	71,1 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.