



TECHNICAL DATA				
EXTERNAL DIMENSIONS				
width	1490 mm			
depth	885 mm			
height	1970/2295mm (door open)			
WEIGHT(basic version)	340 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	14800 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
CROCKERY DIMENSIONS				
size allowed	820 mm			
RACK DIMENSIONS				
1350x725 mm				
RACK EQUIPMENT				
1XC86/A - 1XC97/A - 1X93600				
WASHING CYCLES (min)	1 (3)	2 (6)	3 (9)	4 (12)
WATER SUPPLY 55°C				
racks/h(*) ⁽¹⁾	20	10	6	5
WATER SUPPLY 10°C				
racks/h(*) ⁽¹⁾	10	10	6	5
WATER CONSUMPTION / CYCLE	8,6 L			
BOILER CAPACITY	20 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	148 L			
TANK HEATING ELEMENT	9000 W			
TANK TEMPERATURE (SET)	55°C			
WASHING PUMP POWER	2900 W (950 L/min ^{***}) x 2			
RINSING PUMP POWER	250 W (150 L/min ^{***}) x 2			
DRAIN PUMP (optional)	190 W (120 L/min ^{***})			
ACOUSTIC PRESSURE	71,9 dB(A)			

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.