



TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	600 mm			
depth	700 mm			
height	1380 mm			
WEIGHT(basic version)	99 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	10120 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
plates diameter	---			
size allowed	440 mm			
RACK DIMENSIONS	500X610 mm			
RACK EQUIPMENT	1XC132 - 1X575005 - 1XC86/A - 1X575010			
WASHING CYCLES (sec)	1 (60)	2 (120)	3 (180)	4 (300)
<b>WATER SUPPLY 55°C</b>				
racks/h(*) <sup>(1)</sup>	60	30	20	12
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(1)</sup>	30	30	20	12
WATER CONSUMPTION / CYCLE	2,6 l			
BOILER CAPACITY	15 l			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	25 l			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	1120 W (630 l/min <sup>***</sup> )			
RINSING PUMP POWER	250 W (150 l/min <sup>***</sup> )			
DRAIN PUMP (optional)	190 W (120 l/min <sup>***</sup> )			
NOISE	63.8 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>(1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.