

WATER CONNECTION 3/4" GAS




DRAINING Ø 24mm



ELECTRICAL SUPPLY

PIEDINO "MARINA" "MARINA" FOOT



TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	460 mm			
depth	550 mm			
height	780 mm			
WEIGHT(basic version)	46,5 kg			
VOLTAGE	230V 50Hz			
POWER REQUIRED	3050 W			
WATER HARDNESS	2-8 °f			
INLET WATER PRESSURE	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
plates diameter	310 mm			
size allowed	310 mm			
RACK DIMENSIONS	400X400 mm			
RACK EQUIPMENT	2XC121 - 1X10728 - 1X15060			
WASHING CYCLES (s)	1 (60)	2 (90)	3 (120)	4 (180)
<b>WATER SUPPLY 55°C</b>				
racks/h(*) <sup>(1)</sup>	60	40	30	20
<b>WATER SUPPLY 10°C</b>				
racks/h(*) <sup>(1)</sup>	20	20	16	16
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1,8 L			
BOILER CAPACITY	5,5 l			
BOILER HEATING ELEMENT	2800 W			
RINSING TEMPERATURE (SET)	70°C		85°C	
TANK CAPACITY	7 L			
TANK HEATING ELEMENT	1100 W			
TANK TEMPERATURE (SET)	55°C			
PUMP POWER	250 W (150 L/min <sup>***</sup> )			
DRAIN PUMP (optional)	25 W h max draining 0,8 m (40 L/min <sup>***</sup> )			
NOISE	59.9±0.7 dB(A)			

(\*) STANDARD TERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

(<sup>1</sup>) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.