

**WATER CONNECTION 3/4" GAS**




**DRAINING Ø 24mm**



**ELECTRICAL SUPPLY**

PIEDINO "MARINA" "MARINA" FOOT

TECHNICAL DATA				
<b>EXTERNAL DIMENSIONS</b>				
width	600 mm			
depth	610 mm			
height	850 mm			
WEIGHT	63.5 kg			
VOLTAGE	400V 3N 50Hz < 380/400V 3 60Hz "Marina" >			
POWER REQUIRED	5150 W			
WATER HARDNESS	2-8 °f			
INLET WATER PRESSURE	200-400 kPa			
<b>CROCKERY DIMENSIONS</b>				
plates diameter	340 mm			
dishes max. height	325 mm/GASTRONORM			
RACK DIMENSION	500X500 mm			
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060			
WASHING CYCLES (sec)	1 (60)	2 (90)	3 (180)**	4 (630)**
<b>WATER SUPPLY 55°C</b>				
racks/h(*) (1)	43	40	20	5
<b>WATER SUPPLY 10°C</b>				
racks/h(*) (1)	20	20	18	5
<b>WATER CONSUMPTION / CYCLE (water pressure 200kPa)</b>				
BOILER CAPACITY	2.3 l			
BOILER HEATING ELEMENT	5.7 l			
BOILER HEATING ELEMENT	4500 W			
RINSING TEMPERATURE (SET)	85°C		90°C	
TANK CAPACITY	16.5 l			
TANK HEATING ELEMENT	2700 W < 2230W "Marina" >			
TANK TEMPERATURE (SET)	55°C		70°C	
PUMP POWER	650 W (340 l/min***)			
DRAIN PUMP (optional)	25 W h MAX draining 0.8 m (40 l/min***)			
NOISE	61,3±0.7 dB(A)			



**(\*) STANDARD TERMOSTOP (\*\*) WITH 70°C IN TANK (\*\*\*) MAXIMUM FLOW RATE**

(1)n case of cold water inlet and/or in case of many consecutive wash cycles, the heating times of the final rinse and wash could be extended until the optimum temperature is reached. As a result, the total time of the wash cycle may increase.