


TECHNICAL DATA						
EXTERNAL DIMENSIONS						
width	600 mm					
depth	610 mm					
height	850 mm					
WEIGHT	65 kg					
VOLTAGE	400V 3N 50Hz < 380/400V 3 60Hz "Marina" >					
POWER REQUIRED	5150 W					
WATER HARDNESS	2-8 °f					
INLET WATER PRESSURE	200-400 kPa					
CROCKERY DIMENSIONS						
plates diameter	340 mm					
dishes max. height	325 mm/GASTRONORM					
RACK DIMENSION	500X500 mm					
RACK EQUIPMENT	1XC40 - 1XC44 - 1X15060					
WASHING CYCLES (s)	1(60)	2(90)	3(120)	4(180)	5(180**)	6(630**)
WATER SUPPLY 55°C						
racks/h(*) ⁽¹⁾	60	40	30	20	20	5
WATER SUPPLY 10°C						
racks/h(*) ⁽¹⁾	25	23	30	20	20	5
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2,3 l					
BOILER CAPACITY	11 l					
BOILER HEATING ELEMENT	4500 W					
RINSING TEMPERATURE (SET)	70°C	85°C			90°C	
TANK CAPACITY	16.5 l					
TANK HEATING ELEMENT	2700 W < 2230W "Marina" >					
TANK TEMPERATURE (SET)	55°C				70°C	
PUMP POWER	650 W < 340 l/min*** >					
DRAIN PUMP (optional)	25 W h MAX draining 0.8 m < 40 l/min*** >					
NOISE	61,3±0.7 dB(A)					



(*) STANDARD TERMOSTOP () WITH 70°C IN TANK (***) MAXIMUM FLOW RATE**

(1) In case of cold water inlet and/or in case of many consecutive wash cycles, the heating times of the final rinse and wash could be extended until the optimum temperature is reached. As a result, the total time of the wash cycle may increase.