



TECHNICAL DATA	CLEAN WATER(**)	PARTIAL DRAINING							CLEAN WATER(**)	
EXTERNAL DIMENSIONS										
width				600 mm						
depth				610 mm						
height				850mm						
WEIGHT(basic version)				64,5 kg						
VOLTAGE				230V 50Hz / 230V V3 50Hz / 400V 3N 50Hz						
POWER REQUIRED				6650 W						
WATER HARDNESS				< 8 °f						
INLET WATER PRESSURE				200 - 400 kPa						
CROCKERY DIMENSIONS										
useful opening (H)				340 mm						
RACK DIMENSIONS				500x500 mm						
RACK EQUIPMENT				1xC40 - 1xC44 - 1x15060						
WASHING CYCLES (sec)	0 ^(***) (21÷680)	H1 (180)	H2 (630)	1(60)	2(120)	3(180)	4(60)	5(120)	6(180)	7(360)
WATER SUPPLY 55°C										
racks/h ^(*) (1)	/	6	4	42	30	20	60	30	20	10
WATER SUPPLY 10°C										
racks/h ^(*) (1)	/	4	4	18	18	18	22	22	9	9
WATER CONSUMPTION/CYCLE	/	7 l	3,5 l	DISHES 3,5 l			GLASSES 3,5 l		CLEAN WATER 7,0 l	
WATER CONDUCTIVITY				> 200 µS / cm						
BOILER CAPACITY				11,0 L						
BOILER HEATING ELEMENT				6000 W						
RINSING TEMPERATURE (SET)	0 ^(***) (70÷90°C)	90°C	87°C	82°C			70°C		82°C	
TANK CAPACITY	10 l	7 l	10 l	10 l					7 l	
TANK HEATING ELEMENT				2100 W						
TANK TEMPERATURE (SET)	0 ^(***) (50÷70°C)	75°C	70°C	60°C						
washing/rinsing PUMPS				650 / 250 W						
DRAIN PUMP				25W h max draining 0,8 m						
NOISE				61,3±0,7 dB(A)						

(*)STANDARD TERMOSTOP/ (**) TOTAL DRAINING EVERY CYCLE / (***) CUSTOM CYCLE

(1) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.