



TECHNICAL DATA	CLEAN WATER(**)		PARTIAL DRAINING							CLEAN WATER(**)		
EXTERNAL DIMENSIONS												
width											600 mm	
depth											610 mm	
height											850mm	
WEIGHT(basic version)											64,5 kg	
VOLTAGE											230V 50Hz / 230V V3 50Hz / 400V 3N 50Hz	
POWER REQUIRED											6650 W	
WATER HARDNESS											< 8 °f	
INLET WATER PRESSURE											200 - 400 kPa	
CROCKERY DIMENSIONS												
useful opening (H)											340 mm	
RACK DIMENSIONS											500x500 mm	
RACK EQUIPMENT											1xC40 - 1xC44 - 1x15060	
WASHING CYCLES (sec)	0 ^(***) (21+680)	H1 (180)	H2 (630)	1(60)	2(120)	3(180)	4(60)	5(120)	6(180)	7(360)		
WATER SUPPLY 55°C												
racks/h ^(*) (¹)	/	---	---	---	---	---	---	---	---	---	---	
WATER SUPPLY 10°C												
racks/h ^(*) (¹)	/	4	4	24	24	20	28	28	12	10		
WATER CONSUMPTION/CYCLE	/	7 l	3,5 l	DISHES 3,5 l			GLASSES 3,5 l		CLEAN WATER 7,0 l			
WATER CONDUCTIVITY												
	> 200 µS / cm											
BOILER CAPACITY												
	11,0 L											
BOILER HEATING ELEMENT												
	6000 W											
RINSING TEMPERATURE (SET)	0 ^(***) (70+90°C)	90°C	87°C	82°C			70°C		82°C			
TANK CAPACITY	10 l	7 l	10 l	10 l					7 l			
TANK HEATING ELEMENT												
	2100 W											
TANK TEMPERATURE (SET)	0 ^(***) (50+70°C)	75°C	70°C	60°C								
washing/rinsing PUMPS												
	650 / 250 W											
DRAIN PUMP												
	25W h max draining 0,8 m											
NOISE												
	61,3±0,7 dB(A)											

(*)STANDARD TERMOSTOP/ (**) TOTAL DRAINING EVERY CYCLE / (***) CUSTOM CYCLE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.