



TECHNICAL DATA	PARTIAL DRAINING						CLEAN WATER(**)		
<b>EXTERNAL DIMENSIONS</b>									
width	600 mm								
depth	610 mm								
height	850mm								
WEIGHT(basic version)	64,5 kg								
VOLTAGE	230V 50Hz / 230V V3 50Hz / 400V 3N 50Hz								
POWER REQUIRED	6650 W								
WATER HARDNESS	< 8 °f								
INLET WATER PRESSURE	200 - 400 kPa								
<b>CROCKERY DIMENSIONS</b>									
<b>useful opening (H)</b>	340 mm								
<b>RACK DIMENSIONS</b>	500x500 mm								
<b>RACK EQUIPMENT</b>	1xC40 - 1xC44 - 1x15060								
WASHING CYCLES (sec)	0(21÷680)(***)	1(60)	2(90)	3(120)	4(60)	5(90)	6(180)	7(360)	
<b>WATER SUPPLY 55°C</b>									
racks/h(*) <sup>(1)</sup>	/	---	---	---	---	---	---	---	
<b>WATER SUPPLY 10°C</b>									
racks/h(*) <sup>(1)</sup>	/	24	24	24	28	28	12	10	
<b>WATER CONSUMPTION/CYCLE</b>	/	DISHES 3,5 l			GLASSES 3,5 l		CLEAN WATER 7,0 l		
<b>WATER CONDUCTIVITY</b>	> 200 µS / cm								
<b>BOILER CAPACITY</b>	11,0 l								
<b>BOILER HEATING ELEMENT</b>	6000 W								
<b>RINSING TEMPERATURE (SET)</b>	70÷90°C(***)	82°C			70°C		82°C		
<b>TANK CAPACITY</b>	10,0 l						7,0 l		
<b>TANK HEATING ELEMENT</b>	2100 W								
<b>TANK TEMPERATURE (SET)</b>	50÷70°C(***)	60°C							
<b>washing/rinsing PUMPS</b>	650 / 250 W								
<b>DRAIN PUMP</b>	25W h max draining 0,8 m								
<b>NOISE</b>	61,3±0,7 dB(A)								

(\*)STANDARD TERMOSTOP/ (\*\*) TOTAL DRAINING EVERY CYCLE / (\*\*\*) CUSTOM CYCLE

(1) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.